

Hi-R-Temp[®] Packaged Hot Water Boilers

SPECIFICATIONS

5,000,000 BTU/HR

DESIGN DETAILS

General Information

Type of Boiler	Coiled Tube
Model Series	5937
Rated Capacity	5,000,000 Btu/hr
Water Capacity	47 gal
Construction Codes	ASME, Hartford, National Board
Boiler Shell Insulation	Mineral Wool Insulation
Approx. Shipping Weight	7,800 lbs

Pressure & Temperature

Pressure	Temperature
Up to 4000 psi	Up to 750° F

Controls

Low Combustion Air Switch, Flame Safeguard Control, Low Water Flow Switch, Coil Temperature Limit Switch, Automatic Time Delay Cooling Cycle, etc.

Burner

Manufacturer	Vapor Power
Fuel	Natural Gas, No. 2 Fuel Oil, or Combination
Type (gas)	Multiple Orifice Nozzle
Type (oil)	Air Atomized

Fuel Specifications:

Oil (No. 2)	141,000 Btu/U.S. gal
Gas	1000 Btu/cu ft
Main Burner	2 psig
Pilot Burner	6" W.C.

Atomizing Air Requirements:

Oil (No. 2)	9 scfm @ 20 psig
Gas	None required

Ignition Type:

Oil & Gas	Electric spark - interrupted gas pilot
-----------	---

Power Requirements

Main Power	230/460/575 VAC, 3 Ph, 60 Hz
Control Power	120 VAC, 1 Ph, 60Hz
HP required by blower	5 HP

Overall Dimensions

L x W x H	91" x 78" x 84"
-----------	-----------------

Performance Data

Fuel Consumption @ Rated Output

Gas	6,250 scfh
Oil (No. 2)	43.9 gal/hr

Turndown Ratios:

Oil & Gas	8 to 1
-----------	--------

Combustion and Ventilating Air Required:

Oil & Gas	1,346 scfm
-----------	------------

Customer Connections

Stack Outlet	16"	O.D.
Water Inlet	3"	Flange
Water Outlet	4"	Flange
Main Gas Supply	2 1/2"	NPT
Pilot Gas Supply	1/2"	NPT
Oil Supply	3/4"	NPT
Oil Return	1/2"	NPT
Atomizing Air	3/8"	NPT
Safety Valve Outlet	1 1/4"	NPT

-Note: varies on application details

VAPOR POWER INTERNATIONAL